

MQL Applicator Selection

Mandatory

Option

①BK applicator(Mandatory)

BK	1
Model	Mist outlets

1 1 port
2 2 ports
Orifice(※1) Mist outlets
1 2

(※1)
Please select BK12 as Mist outlets 2 ports with less quantity of mist than that of BK2 required.
BK21(Orifices2/port1) is NOT supported.




Solenoid Valve (Opton) ※2

Blank	No valve
S1	100VAC
S2	200VAC
S3	24VDC

(※2)
· Specification: 2 port valve. (VX220AF type)
· NOT in Stock parts
· Please contact us when solenoid valve required.

BLLMB


Nozzle
(Dedicated nozzle required)

 BLLMB Loc-Line Nozzle with magnet base for BK	Blank standard length (330mm) (20knuckles)	XX customized length (□□mm) (XXknuckles) (※3)
 BLLM6SB Loc-Line Nozzle with M6 stadbase for BK		
 BLL Loc-Line Nozzle for BK (※4)	20 standard length (330mm) (20knuckles)	XX customized length (□□mm) (XXknuckles) (※3)

(※3)Specify number of knuckles(length) when non-standard length is offered. Please contact us detailed specifications.
· Nozzle length = 14.5mm x(knuckles) +40mm
· Nozzle length vary on number of knuckles.

(※4)NOTES for BLL
· BLL offers connection destination because BLL Unit has no magnet or mount kit oneself.
· Specify number of knuckles (Fill in 20 even standard length offered)

②Optional parts

Filter Regulator	How to Fix Applicator	Options
Blank NOT Equipped (Standard)	Blank (※2) (Standard)	SP Special Specification
FR Equipped	 MG Magnets (※2) Mounted by M6-screws	



BK2-BLLMB

Soft nylon tubing(3m)for delivering mist is packed with BK applicator.
Please contact us for inquires of mist tubing length being 3m over required.

 NBCS 12BF Circular saw nozzle for BK (1 inlet-2outlets)	 NBBS 13BF25 Band saw nozzle for BK (Blade width:25mm)	NN No nozzle
 NBCS 22BF Circular saw nozzle for BK (2inlets-2outlets)	 NBBS 13BF38 Band saw nozzle for BK (Blade width:38mm)	